



GENERAL LOCK® ED9000/EDX9000 RIM FIRE RATED EXIT DEVICE INSTALLATION TEMPLATE

- 3/16"-24x1"(25.4mm) (1-3/4"DOOR)
- 3/16"-24x1-1/2"(38.1mm) (2-1/4"DOOR)
- (Tap 3/16"-24)
- Sex Bolt 3/16" (Drill Ø3/8"(Ø9.5mm))
- #10 TYPE AB x 1-1/4"L(32mm) (Drill Ø1/8"(Ø3.2mm))

- 3/16"-24x 3/4"(19mm) (1-3/4"DOOR)
- 3/16"-24x1-1/4"(32mm) (2-1/4"DOOR)
- (Tap 3/16"-24)
- Sex Bolt 3/16" (Drill Ø3/8"(Ø9.5mm))
- #10 TYPE AB x 1-1/4"L(32mm) (Drill Ø1/8"(Ø3.2mm))

- #10-24 x 5/8"L(15.9mm) (Tap #10-24)
- #10-12 x 1-1/2"L(38mm) (Drill Ø1/8"(Ø3.2mm))

FOR 3'x10'(ft) Door : 30-3/4" (780mm)
 FOR 4'x10'(ft) Door : 42-3/4" (1085mm)