

Sirens and Strobes

- **High Output Performance:** Loud decibel rating with single or dual tone options for clear alerts.
- **Wide Compatibility:** Operates across standard DC voltage ranges with low current draw.
- **Durable Construction:** Weather-resistant housings designed for indoor or outdoor use.
- **Flexible Installation:** Compact form factors with multiple mounting options.
- **Reliable Safety Signaling:** Provides immediate audio/visual alerts in emergency situations.



D15WU-GL



D20WU-GL



SS120-BL-WP



D30WU-GL



S20WU-GL

SKU#	Power	Decibels	Current	Voltage	Dimensions (DxLxH)		Weight		Weatherproof Rating	Signal Type
					(in.)	(mm)	(lbs.)	(g)		
D15WU-GL	15 Watt	108 dB ± 5	500 ± 100 mA	6~13.5 Volts DC	4.3 x 2.36 x 4.3	110 x 60 x 110	1.05	440	Indoor Only	Yelp and Steady Tone
D20WU-GL	20 Watt	115 dB (max)	750~950 mA	6~13.5 Volts DC	Φ5.3 x 5.9 x 6.1	Φ135 x 150 x 155	1.05	480	IP 55	Yelp and Steady Tone
D30WU-GL	30 Watt	120 dB ± 5	800~1200 mA	6~13.5 Volts DC	8.66 x 9.44 x 6.7	220 x 240 x 170	2.8	560	IP 55	Yelp and Steady Tone
S20WSU-GL	20 Watt	115 dB (max)	750~950 mA	6~13.5 Volts DC	Φ5.3 x 5.9 x 6.1	Φ135 x 150 x 155	1.05	480	IP 55	Yelp
SS120-BL-WP	25 Watt	120	190 mA	9~15 Volts DC	6.13 x 7 x 4.5	155 x 178 x 115	2.2	957	IP 65	Blue Strobe

250114D063